

VARI-FOCAL

VARI-FOCAL COLOR CAMERA



1/3" Color Exview 480TVL, 2x Vari-focal, 0.2 Lux

V-8HAP

1/3" Color Exview 380TVL, 2x Vari-focal, 0.2 Lux

V-8MAP

1/3" Color 480TVL, 2X Vari-focal, 1.0 Lux

V-68AP

1/3" Color 380TVL, 2X Vari-focal, 1.0 Lux

V-66AP

Features

- ▼ Full range Sony 1/3" Exview HAD & Super HAD CCD camera
- ▼ Flexible built-in vari-focal auto-iris lens for versatile environment applications
- ▼ Compact camera functions of ATW/AWB, BLC on/off, AGC on/off
- ▼ Easy installation design
- ▼ User-friendly lens adjustment
- ▼ AC 24V/DC 12V two power sources (DC 12V default, AC 24V option)

Specifications

Model	KD-8HAP	KD-8MAP			D-68AP	D-66AP		
Image device	1/3" Interline Transfer Sony Exview HAD CCD				1/3" Interline Transfer Sony Super HAD CCD			
Signal system	PAL				PAL			
Picture elements	795(H)x596(V)	542(H)x582(V)			795(H)x596(V)	542(H)x582(V)		
Scanning system	2:1 Interlace 625 lines,	2:1 Interlace 625 lines,			2:1 Interlace 625 lines,	2:1 Interlace 625 lines,		
Sync system	Internal lock							
Horizontal resolution	480 TV lines	380 TV lines			480 TV lines	380 TV lines		
Minimum illumination	0.2 lux at F1.4 (30 IRE, AGC ON)				1 lux at F1.4 (30 IRE, AGC ON)			
S/N ratio	Better than 48dB							
Auto iris mode	1/50 sec.				1/50 sec.			
Auto iris lens type	DC Drive							
White balance	ATW2500°K~9500°K							
Focal length	3.5-8mm							
Iris range	F1.6							
Backlight compensation	Auto Detect On/Off;							
Video output signal	BNC, 1.0 V p-p at 75 Ω load							
Operating temperature	-10°C to 50°C RH80%							
Power source	DC 12V							
Power consumption	3.5W							
Dimensions (W x H x D)	57 x 52 x 116 mm							

Dimensions

